FDF1140A



 ${f T-27}$ - Used for grinding flat surfaces. Most efficient when used at a 0-15 degree angle.

- · High quality cloth & premium Aluminum oxide grains
- · Consistent Cutting rate with min. Heat generation
- · Long Life with consistence surface finish.
- · Less operational cost
- · High Quality Fiber glass backing

| PRODUCT CODE | FDF1140A |
|---|---|
| PRODUCT USAGE | Surface Finish |
| PRODUCT DIMENSION | 115x 22.23 mm |
| DAIMETER | 115 mm |
| Hole | 22.23 mm |
| Grit Size | 40 |
| PRODUCT WEIGHT | 72 gms. (with Standard tolerance) |
| PRODUCT TYPE | TYPE 27 |
| PRODUCT SHAPE DESCRIPTION | Flat flap disc |
| MAXIMUM OPERATING SPEED | 80 m/s |
| MAXIMUM REVOLUTION | 13,300 U/min |
| PRODUCT SUITABILITY | METAL/CARBON STEEL/ Aluminum |
| INDUSTRIAL SUITABILITY OF PRODUCT | FOUNDRY & DRESSING, SITE CONSTRUCTION, SHIPYARD, PIPE CONSTRUCTION (Weld removal and blending of all types of metal Fabrications for light duty applications) |
| STANDARD FOLLOWING FOR ABRASIVE MARKING | EN13743 |
| TYPE OF PACKING | CARTON |
| PIECES PER PACKING | 200 PCS |
| NET WEIGHT OF PACKING UNIT | 14.755 Kgs |
| CUSTOMS TARIFF NUMBER | 68042200 |
| COUNTRY OF ORGIN | KSA |





FDF1160A



T-27 - Used for grinding flat surfaces. Most efficient when used at a 0-15 degree angle.

- · High quality cloth & premium Aluminum oxide grains
- · Consistent Cutting rate with min. Heat generation
- · Long Life with consistence surface finish.
- · Less operational cost
- · High Quality Fiber glass backing

| PRODUCT CODE | FDF1160A |
|--|---|
| PRODUCT USAGE | Surface Finish |
| PRODUCT DIMENSION | 115x 22.23 mm |
| DAIMETER | 115 mm |
| Hole | 22.23 mm |
| Grit Size | 60 |
| PRODUCT WEIGHT | 68 gms. (with Standard tolerance) |
| PRODUCT TYPE | TYPE 27 |
| PRODUCT SHAPE DESCRIPTION | Flat flap disc |
| MAXIMUM OPERATING SPEED | 80 m/s |
| MAXIMUM REVOLUTION | 13,300 U/min |
| PRODUCT SUITABILITY | METAL/CARBON STEEL/ Aluminum |
| | |
| INDUSTRIAL SUITABILITY OF PRODUCT | FOUNDRY & DRESSING, SITE CONSTRUCTION, SHIPYARD, PIPE CONSTRUCTION (Weld removal and blending of all types of metal Fabrications for light duty applications) |
| INDUSTRIAL SUITABILITY OF PRODUCT STANDARD FOLLOWING FOR ABRASIVE MARKING | FOUNDRY & DRESSING, SITE CONSTRUCTION, SHIPYARD, PIPE CONSTRUCTION (Weld removal and blending of all |
| | FOUNDRY & DRESSING, SITE CONSTRUCTION, SHIPYARD, PIPE CONSTRUCTION (Weld removal and blending of all types of metal Fabrications for light duty applications) |
| STANDARD FOLLOWING FOR ABRASIVE MARKING | FOUNDRY & DRESSING, SITE CONSTRUCTION, SHIPYARD, PIPE CONSTRUCTION (Weld removal and blending of all types of metal Fabrications for light duty applications) EN13743 |
| STANDARD FOLLOWING FOR ABRASIVE MARKING TYPE OF PACKING | FOUNDRY & DRESSING, SITE CONSTRUCTION, SHIPYARD, PIPE CONSTRUCTION (Weld removal and blending of all types of metal Fabrications for light duty applications) EN13743 CARTON |
| STANDARD FOLLOWING FOR ABRASIVE MARKING TYPE OF PACKING PIECES PER PACKING | FOUNDRY & DRESSING, SITE CONSTRUCTION, SHIPYARD, PIPE CONSTRUCTION (Weld removal and blending of all types of metal Fabrications for light duty applications) EN13743 CARTON 200 PCS |





FDF1180A



T-27 - Used for grinding flat surfaces. Most efficient when used at a 0-15 degree angle.

- · High quality cloth & premium Aluminum oxide grains
- · Consistent Cutting rate with min. Heat generation
- · Long Life with consistence surface finish.
- · Less operational cost
- · High Quality Fiber glass backing

| PRODUCT CODE | FDF1180A |
|---|---|
| PRODUCT USAGE | Surface Finish |
| PRODUCT DIMENSION | 115x 22.23 mm |
| DAIMETER | 115 mm |
| Hole | 22.23 mm |
| Grit Size | 80 |
| PRODUCT WEIGHT | 65 gms. (with Standard tolerance) |
| PRODUCT TYPE | TYPE 27 |
| PRODUCT SHAPE DESCRIPTION | Flat flap disc |
| MAXIMUM OPERATING SPEED | 80 m/s |
| MAXIMUM REVOLUTION | 13,300 U/min |
| PRODUCT SUITABILITY | METAL/CARBON STEEL/ Aluminum |
| INDUSTRIAL SUITABILITY OF PRODUCT | FOUNDRY & DRESSING, SITE CONSTRUCTION, SHIPYARD, PIPE CONSTRUCTION (Weld removal and blending of all types of metal Fabrications for light duty applications) |
| STANDARD FOLLOWING FOR ABRASIVE MARKING | EN13743 |
| TYPE OF PACKING | CARTON |
| PIECES PER PACKING | 200 PCS |
| NET WEIGHT OF PACKING UNIT | 13.355 Kgs |
| CUSTOMS TARIFF NUMBER | 68042200 |
| COUNTRY OF ORGIN | KSA |





FDF11100A



T-27 - Used for grinding flat surfaces. Most efficient when used at a 0-15 degree angle.

- · High quality cloth & premium Aluminum oxide grains
- · Consistent Cutting rate with min. Heat generation
- · Long Life with consistence surface finish.
- · Less operational cost
- · High Quality Fiber glass backing

| PRODUCT CODE | FDF11100A |
|---|---|
| PRODUCT USAGE | Surface Finish |
| PRODUCT DIMENSION | 115x 22.23 mm |
| DAIMETER | 115 mm |
| Hole | 22.23 mm |
| Grit Size | 100 |
| PRODUCT WEIGHT | 65 gms. (with Standard tolerance) |
| PRODUCT TYPE | TYPE 27 |
| PRODUCT SHAPE DESCRIPTION | Flat flap disc |
| MAXIMUM OPERATING SPEED | 80 m/s |
| MAXIMUM REVOLUTION | 13,300 U/min |
| PRODUCT SUITABILITY | METAL/CARBON STEEL/ Aluminum |
| INDUSTRIAL SUITABILITY OF PRODUCT | FOUNDRY & DRESSING, SITE CONSTRUCTION, SHIPYARD, PIPE CONSTRUCTION (Weld removal and blending of all types of metal Fabrications for light duty applications) |
| STANDARD FOLLOWING FOR ABRASIVE MARKING | EN13743 |
| TYPE OF PACKING | CARTON |
| PIECES PER PACKING | 200 PCS |
| NET WEIGHT OF PACKING UNIT | 13.355 Kgs |
| CUSTOMS TARIFF NUMBER | 68042200 |
| COUNTRY OF ORGIN | KSA |





FDF11120A



T-27 - Used for grinding flat surfaces. Most efficient when used at a 0-15 degree angle.

- · High quality cloth & premium Aluminum oxide grains
- · Consistent Cutting rate with min. Heat generation
- · Long Life with consistence surface finish.
- · Less operational cost
- · High Quality Fiber glass backing

| PRODUCT CODE | FDF11120A |
|---|---|
| PRODUCT USAGE | Surface Finish |
| PRODUCT DIMENSION | 115x 22.23 mm |
| DAIMETER | 115 mm |
| Hole | 22.23 mm |
| Grit Size | 120 |
| PRODUCT WEIGHT | 61 gms. (with Standard tolerance) |
| PRODUCT TYPE | TYPE 27 |
| PRODUCT SHAPE DESCRIPTION | Flat flap disc |
| MAXIMUM OPERATING SPEED | 80 m/s |
| MAXIMUM REVOLUTION | 13,300 U/min |
| PRODUCT SUITABILITY | METAL/CARBON STEEL/ Aluminum |
| INDUSTRIAL SUITABILITY OF PRODUCT | FOUNDRY & DRESSING, SITE CONSTRUCTION, SHIPYARD, PIPE CONSTRUCTION (Weld removal and blending of all types of metal Fabrications for light duty applications) |
| STANDARD FOLLOWING FOR ABRASIVE MARKING | EN13743 |
| TYPE OF PACKING | CARTON |
| PIECES PER PACKING | 200 PCS |
| NET WEIGHT OF PACKING UNIT | 12.555 Kgs |
| CUSTOMS TARIFF NUMBER | 68042200 |
| COUNTRY OF ORGIN | KSA |



