

PRODUCT DATA SHEET

FW251560



Product Features:

- Premium quality of grains for high stock removal
- High strength adhesion for high speed performance
- High quality steel spindle to withstand high speed.
- Available in different sizes to suit typical applications.

Best product with a moderate cost for professional works with excellent performance.

PRODUCT CODE	FW251560
PRODUCT USAGE	De-burring & cleaning applications
PRODUCT DIMENSION	DIA 25 mm
Thickness	20, 25, 30 mm
Spindle Size	6 mm
Grit Size	40, 60, 80, 100 & 120 mm
PRODUCT WEIGHT	17 – 20 gms
PRODUCT TYPE	With Spindle
PRODUCT SHAPE DESCRIPTION	Flapper wheel
MAXIMUM OPERATING SPEED	80 m/s
MAXIMUM REVOLUTION	30,500 RPM
PRODUCT SUITABILITY	METAL/CARBON STEEL/ Aluminum/ Stainless steel
INDUSTRIAL SUITABILITY OF PRODUCT	widely used for de-burring, cleaning applications in metal fabrication industries and finishing of hard to reach areas such as internal surface of pipes, cylinders, moulds etc.,
STANDARD FOLLOWING FOR ABRASIVE MARKING	EN13743
TYPE OF PACKING	CARTON
PIECES PER PACKING	400 Nos
NET WEIGHT OF PACKING UNIT	13.9 to 16.3 Kgs
CUSTOMS TARIFF NUMBER	68042200
COUNTRY OF ORIGIN	KSA

Note: Min.- Max. Dia.: 20-100 mm
Min.- Max. Thickness: 5 - 60 mm
Non - standard sizes are available on request