

PRODUCT DATA SHEET

FW804080



Product Features:

- Premium quality of grains for high stock removal
- High strength adhesion for high speed performance
- High quality steel spindle to withstand high speed.
- Available in different sizes to suit typical applications.

Best product with a moderate cost for professional works with excellent performance.

| | |
|---|---|
| PRODUCT CODE | FW804080 |
| PRODUCT USAGE | De-burring & cleaning applications |
| PRODUCT DIMENSION | DIA 80 mm |
| Thickness | 20, 25, 30 mm |
| Spindle Size | 6 mm |
| Grit Size | 40, 60, 80, 100 & 120 mm |
| PRODUCT WEIGHT | 84 - 130 gms |
| PRODUCT TYPE | With Spindle |
| PRODUCT SHAPE DESCRIPTION | Flapper wheel |
| MAXIMUM OPERATING SPEED | 80 m/s |
| MAXIMUM REVOLUTION | 9,500 RPM |
| PRODUCT SUITABILITY | METAL/CARBON STEEL/ Aluminum/ Stainless steel |
| INDUSTRIAL SUITABILITY OF PRODUCT | widely used for de-burring, cleaning applications in metal fabrication industries and finishing of hard to reach areas such as internal surface of pipes, cylinders, moulds etc., |
| STANDARD FOLLOWING FOR ABRASIVE MARKING | EN13743 |
| TYPE OF PACKING | CARTON |
| PIECES PER PACKING | 100 Nos |
| NET WEIGHT OF PACKING UNIT | 8.7 to 13.4 Kgs |
| CUSTOMS TARIFF NUMBER | 68042200 |
| COUNTRY OF ORIGIN | KSA |

Note: Min.- Max. Dia.: 20-100 mm
Min.- Max. Thickness: 5 - 60 mm
Non - standard sizes are available on request